



Busch PROtective
USA



Tech Specs

Material	Dupont Kevlar Fiber with Ebsp-Technology
Style	High-Cut (available in Midcut & Fullcut)
Coating	2K- Paint
Edge Protection	EPDM rubber edge
Colours	black, green  
Weight* (HC)	1580 g - 3.4 lbs including inside equipment 1680 g - 3.7 lbs including rail system
Shock Absorbition	CPP-1 or CPP-2 TP Pad System
Harness System	CRS-2 Harness System
Size	Unisize 52 - 63 cm / 6 1/2 to 8
Interfaces	CMR-1 Rail System

*helmet weight has natural tolerances of ±50 g - 1.7 ounces

AMP-1 TP

NIJ IIIA + DEA/FBI PROTOCOL +
VPAM Ballistic Helmet

Ballistic Protection	-      +
Energy Transmission	-      +
Protective Area	-      +
Modularity	-      +
Weight	-      +

Standards / Certifications

US Ballistic:	NIJ-STD-0106.01 IIIA, NIJ-STD-0108.01 (Chesapeake) DEA-FBI Ballistic Helmet Protocol 2019 Certified
European Ballistic:	VPAM- HVN 2009, Level 3
Fragmentation:	STANAG 2920, 1,1g Splitter: V50= 630 m/s - 2066 fps
Impact:	Shock absorbing according to DIN EN 397
Also:	3.1 TR Gesamtsystem „Ballistischer Helm“ Date Mai 2010 3.2, 3.4, 3.5 TR Gesamtsystem „Ballistischer Helm“ Date Mai 2010

Special Properties | Accessories

- heat-resistant helmet shell
- extremely robust helmet shell using patented Ebsp-Technology, complete with full ballistic bolts
- compatible with most gas masks and hearing protection
- helmet bag included as standard
- SCS (Speed-Connect-System) visor mount compatible with all visor models

additional accessories: NVG-shrouds, velcro kit, bungees, AK rifle Plate, Pelitor adapter, harness extender, visors, helmet covers, counter weights, TTB-1 tactical helmet bag