




Tech Specs

Material	Fibre reinforced duroplast
Coating	2K- paint scratch & chemical resistance
Style	Full-Cut Anti Riot Shape
Edge Protection	EPDM rubber edge
Colours	black, olive green, midnight blue, white 
Weight*	1350 g / 2.98 lbs with inside equipment, Neck Guard, Rails and Visor (3mm)
Shock Absorbtion	CPP-1 Pad System
Harness System	CRS-2 Harness System
Size	Unisize 52 - 62 cm / 6 1/2 to 8
Interfaces	CRR-1 modular Railsystem

AMR-1 E

Anti Riot Helmet

Shock Absorbing	-		+
Penetration Resistance	-		+
Fragment Protection	-		+
Protective Area	-		+
Weight	-		+

Standards / Certifications

shock absorption according to EN 397, 5.1.1
 resistance to penetration according to EN 397, 5.1.2
 flame resistance according to EN 397, 5.1.3
 lateral deformation according to E 397, 5.2.4

blunt impact resistance and resistance to penetration have been performed at
 -10°C (6.2.3), water immersion +20°C (6.2.5) and +50°C (6.2.4)

Special Properties | Accessories

protection against penetration
 blunt impact protection
 heat-resistant helmet shell
 well ventilated pad system with air vents
 3 mm (or thicker) visor with anti scratch and anti fog coating
 removable neck protection

CRR.1 (Riot Rail System) with fixed visor mount, gas mask and multi functional rail

additional accessories: flashlights, cameras, gas masks and helmet bags



Busch PROtective