



## 

Tech Specs	
Material	Kevlar Fiber
Coating	2K- paint scratch & chemical resistance
Style	Full-Cut Anti Riot Shape
Edge Protection	EPDM rubber edge
Colours	black, olive green, midnight blue, white
Weight*	1,98 kg / 4.36 lbs including inside equipment, Neck Guard, Rails and Visor (3mm)
Shock Absorbtion	CPP-1 R Pad System
Harness System	CRS-2 Harness System
Size	Unisize 52 - 62 cm / 6 <sup>1</sup> / <sub>2</sub> to 8
Interfaces	CRR-1 Railsystem

## Standards / Certifications

- ballistic protection against 9 mm rounds according to NIJ-STD-0106.01 IIIA, NIJ-STD-0108.01 (Chesapeake)
- STANAG 2920, 17 grain fragment: V50= 600+ m/s 1968+ fps
- shock absorption according to EN 397, 5.1.1
- resistance to penetration according to EN 397, 5.1.2
- flame resistance according to EN 397, 5.1.3
- lateral deformation according to E 397, 5.2.4
- shock absorption and resistance to penetration have been performed at -10°C (6.2.3), water immersion +20°C (6.2.5) and +50°C (6.2.4)

## **Special Properties | Accessories**

high level of protection against penetration
high level of blunt impact protection
heat-resistant helmet shell
good ventilation thanks pad system with air ducts

3 mm or thicker visor ( with anti s**c**ratch and anti fog coating removable neck protection

CRR.1 (Riot Rail System) with fixed visor mount, gas mask and multi functional rail

additional accessories: flashlights, cameras and gas masks

